

KELLO-BILT

TILLAGE EQUIPMENT

MODEL 500 & 600

SINGLE OFFSET BREAKING DISC



FEATURES

MASSIVE WELDMENTS / SUPERIOR COMPONENTS

The Kello-Bilt Model 500/600 offset disc is specifically designed to meet the extreme conditions encountered in the construction industry. For over 25 years these rugged discs have been employed to clear land, build roads and dams, reclaim mine sites, mix and dry soils, and prepare land for reforestation throughout North America.

EXCLUSIVE OIL-BATH BEARING SYSTEM

Back to back tapered bearings in large cast steel housings and sealed with floating metal oil seals. Tapered bearings are designed for thrust unlike ball bearings used by other manufacturers. Oil-Bath bearings provide a low maintenance, high quality solution that is essential in any industrial application.



FIELD TESTED & PROVEN FOR OVER 30 YEARS. YOU WANT THE BEST, YOU HAVE THE BEST WITH...

KELLO-BILT

MODEL 500 & 600

SINGLE OFFSET BREAKING DISC

Model 500 Single offset breaking disc

Model 600 Single offset breaking disc

Specifications

- Frame..... 8" x 8" x 1/2" high strength steel tube frame, 7" x 7" x 1/2" high strength steel tube gang bars, fully welded and reinforced.
- Bearings..... Oil bath, back to back tapered roller bearings in heavy ductile cast housing c/w floating Duo-Cone® seals. Bearings operate in 90W gear oil for constant lubrication. Bearing comes complete with wear plate. Size: Model 500 – 14", Model 600 – 17".
- Gang Shaft..... 2 - 1/2" heat treated high strength alloy steel, threaded at both ends.
- Spacing..... Model 500 - 14" fabricated heavy steel spacer spools designed to maintain gang tightness.
Model 600 - 17" fabricated heavy steel spacer spools designed to maintain gang tightness.
- Disc Blades..... Model 500 – 1/2" x 32" notched disc blades front and rear.
Model 600 - 1/2" x 36" notched disc blades front and rear.
- Hubs/Tires..... Goodyear™ 385/65R22.5 Super Single Radial heavy industrial tires mounted on 5 spoke Dayton™ hubs.
- Hydraulics..... 5" x 20" hydraulic cylinder complete with hoses, depth control segments and cylinder transport lock.
- Standard..... 7000lb hitch jack, plated grade 8 fasteners, gang wrench (2), separate fore/aft and transport level controls, and a heavy swivel flapper hook-up.

Model Number	Cut Width	Approx. Weight	Approx. Lbs/Blade*	Approx D.B.H.P**
500-2332B	12'	12,500 lbs	595	250 plus
500-2532B	13'6"	13,300 lbs	578	300 plus
600-1936B	12'	14,500 lbs	853	275 plus
600-2136B	13'6"	15,200 lbs	800	325 plus

*Does not include tapered furrow filler discs.

**Drawbar horsepower requirements vary with soil conditions, topography, weight added to harrow, and tractor type (steel track, rubber track, or rubber tire).

Kello-Bilt Inc. reserves the right to change pricing and specifications without notice.



Phone: (403) 347-9500 Fax: (403) 347-3724

Toll Free: 1-877-613-9500

E-mail: info@kello-bilt.com

Web: www.kello-bilt.com

#16 - 37337 Burnt Lake Trail, Red Deer County, AB Canada T4S 2K5

Sold & Serviced By: